

Požadujeme, aby všetky ocenené diskové polia boli iba od jedného výrobcu t.j. buď Dell, IBM, Lenovo alebo HPE (iný výrobca sa nepripúšťa)

Typ: Diskové pole (centrálna lokalita)	
Minimálne technické požiadavky	Splnené minimálne technické požiadavky položky predmetu zákazky (áno/nie)
	vyplní účastník
all-flash end-to-end NVMe úložisko montované do štandardného 19" racku podpora minimálne RAID 5,6 napájanie redundantné 2x 1450W, jednoúčelové do 250V všetky kľúčové komponenty musia byť redundantné, vymeniteľné a rozšíriteľné bez nutnosti odstávky konektivita 16Gb FC, celkovo aspoň 8 portov aktiv-aktiv kontroly dátová Cache min. 192GB, chránená proti výpadku napájania hardware-accelerated kompresná technológia, zapnutie bez dopadu na výkonosť pola podpora deduplikáciej technológie štandardný aj thin provisioning LUNov, vytváranie snapshotov a klonov LUNov pri poruche jedného kontrolra ďalší prevzame automaticky celú jeho funkcionallitu výmena kontrolérov musí byť bez prerušenia funkcionality aktualizácia SW a FW diskov musí byť bez prerušenia funkcionality multitpath ovládacie pre OS MS, vmware musia byť zahrnuté v cene osadená disková kapacita v RAID6 s aspoň 1 Hot-Spare min 30TB bez kompresie a deduplikácie, rozšíriteľná na min. 50TB iba pridaním ďalších NVMe diskov	áno

Typy Diskové pole (malíš lokalitte)																																																							
Miniálné technické požiadavky	Ponuka účastníka (účastník môže predložiť aj kvalitatívne lepšie riešenie, ktoré bude spĺňať daný parameter/požiadavku). Požaduje sa uviesť skutočnú špecifikáciu ponúkaného predmetu záskazy – výrobu, typové označenie a technické parametre. V prípade číselnej hodnoty uviesť jej skutočnú hodnotu <table border="1"> <thead> <tr> <th>vyplní účastník</th> <th>Splnené minimálne technické požiadavky položky predmetu záskazy (áno/nie)</th> </tr> </thead> <tbody> <tr> <td>All-flash (SAS SSD disky sú akceptované)</td> <td>áno</td> </tr> <tr> <td>montované do štandardného 19" racku</td> <td>áno</td> </tr> <tr> <td>podpora minimálne RAID 5,6</td> <td>áno</td> </tr> <tr> <td>nápasanie redundantné, jednorázové do 250V</td> <td>áno</td> </tr> <tr> <td>všetky kľúčové komponenty musia byť redundantné, vymeniteľné a rozšíriteľné bez nutnosti odstávky</td> <td>áno</td> </tr> <tr> <td>konektivita 16Gb FC, celkovo aspoň 4 porty</td> <td>áno</td> </tr> <tr> <td>dátová Cache min. 64GB, chránená pre prípad výpadku napájania batériou</td> <td>áno</td> </tr> <tr> <td>štandardný aj thin provisioning LUNov,</td> <td>áno</td> </tr> <tr> <td>vychádzanie snapshotov a klonov LUNov</td> <td>áno</td> </tr> <tr> <td>pri poruche jediného kontroléra ďalší prevzme automaticky celý jeho funkcionalitu</td> <td>áno</td> </tr> <tr> <td>výmena kontrolierov musí byť bez prerušenia funkcionality</td> <td>áno</td> </tr> <tr> <td>aktualizácia SW a FW diskov musí byť bez prerušenia funkcionality</td> <td>áno</td> </tr> <tr> <td>multipath ovládacie pre OS MS, vmware</td> <td>áno</td> </tr> <tr> <td>rozšírenie podponje natívne multipath ovládace pre OS MS, vmware</td> <td>áno</td> </tr> <tr> <td>osadenia disková kapacita v RAID6 min. 5TB bez kompresie a deduplikácie, rozšíriteľná na 10TB iba pridaním ďalších diskov</td> <td>áno</td> </tr> <tr> <td>Iné</td> <td>áno</td> </tr> <tr> <td>Záruka 36 mesiacov,</td> <td>áno</td> </tr> <tr> <td>Cena</td> <td>Príchod - Diskové pole 2 22 720,00 € 5 340,00 € 4 865,00 € 3 902,00 € 1 495,00 € 1 495,00 €</td> </tr> <tr> <td>Ponúkaná konfigurácia</td> <td></td> </tr> <tr> <td>Cena bez DPH za ponúkajú konfiguráciu Diskového pola (malíš lokalita)</td> <td></td> </tr> <tr> <td>SLA1 na 1 rok</td> <td></td> </tr> <tr> <td>SLA2 na 1 rok (táto položka bude v aukcii súťažena)</td> <td></td> </tr> <tr> <td>SLA3 na 1 rok</td> <td></td> </tr> <tr> <td>SLA4 na 1 rok</td> <td></td> </tr> <tr> <td>SLA5 na 1 rok</td> <td></td> </tr> <tr> <td>Výrobca a model + kód produktu:</td> <td>Dell PowerStore 500T, 210AXXU</td> </tr> </tbody> </table>	vyplní účastník	Splnené minimálne technické požiadavky položky predmetu záskazy (áno/nie)	All-flash (SAS SSD disky sú akceptované)	áno	montované do štandardného 19" racku	áno	podpora minimálne RAID 5,6	áno	nápasanie redundantné, jednorázové do 250V	áno	všetky kľúčové komponenty musia byť redundantné, vymeniteľné a rozšíriteľné bez nutnosti odstávky	áno	konektivita 16Gb FC, celkovo aspoň 4 porty	áno	dátová Cache min. 64GB, chránená pre prípad výpadku napájania batériou	áno	štandardný aj thin provisioning LUNov,	áno	vychádzanie snapshotov a klonov LUNov	áno	pri poruche jediného kontroléra ďalší prevzme automaticky celý jeho funkcionalitu	áno	výmena kontrolierov musí byť bez prerušenia funkcionality	áno	aktualizácia SW a FW diskov musí byť bez prerušenia funkcionality	áno	multipath ovládacie pre OS MS, vmware	áno	rozšírenie podponje natívne multipath ovládace pre OS MS, vmware	áno	osadenia disková kapacita v RAID6 min. 5TB bez kompresie a deduplikácie, rozšíriteľná na 10TB iba pridaním ďalších diskov	áno	Iné	áno	Záruka 36 mesiacov,	áno	Cena	Príchod - Diskové pole 2 22 720,00 € 5 340,00 € 4 865,00 € 3 902,00 € 1 495,00 € 1 495,00 €	Ponúkaná konfigurácia		Cena bez DPH za ponúkajú konfiguráciu Diskového pola (malíš lokalita)		SLA1 na 1 rok		SLA2 na 1 rok (táto položka bude v aukcii súťažena)		SLA3 na 1 rok		SLA4 na 1 rok		SLA5 na 1 rok		Výrobca a model + kód produktu:	Dell PowerStore 500T, 210AXXU
vyplní účastník	Splnené minimálne technické požiadavky položky predmetu záskazy (áno/nie)																																																						
All-flash (SAS SSD disky sú akceptované)	áno																																																						
montované do štandardného 19" racku	áno																																																						
podpora minimálne RAID 5,6	áno																																																						
nápasanie redundantné, jednorázové do 250V	áno																																																						
všetky kľúčové komponenty musia byť redundantné, vymeniteľné a rozšíriteľné bez nutnosti odstávky	áno																																																						
konektivita 16Gb FC, celkovo aspoň 4 porty	áno																																																						
dátová Cache min. 64GB, chránená pre prípad výpadku napájania batériou	áno																																																						
štandardný aj thin provisioning LUNov,	áno																																																						
vychádzanie snapshotov a klonov LUNov	áno																																																						
pri poruche jediného kontroléra ďalší prevzme automaticky celý jeho funkcionalitu	áno																																																						
výmena kontrolierov musí byť bez prerušenia funkcionality	áno																																																						
aktualizácia SW a FW diskov musí byť bez prerušenia funkcionality	áno																																																						
multipath ovládacie pre OS MS, vmware	áno																																																						
rozšírenie podponje natívne multipath ovládace pre OS MS, vmware	áno																																																						
osadenia disková kapacita v RAID6 min. 5TB bez kompresie a deduplikácie, rozšíriteľná na 10TB iba pridaním ďalších diskov	áno																																																						
Iné	áno																																																						
Záruka 36 mesiacov,	áno																																																						
Cena	Príchod - Diskové pole 2 22 720,00 € 5 340,00 € 4 865,00 € 3 902,00 € 1 495,00 € 1 495,00 €																																																						
Ponúkaná konfigurácia																																																							
Cena bez DPH za ponúkajú konfiguráciu Diskového pola (malíš lokalita)																																																							
SLA1 na 1 rok																																																							
SLA2 na 1 rok (táto položka bude v aukcii súťažena)																																																							
SLA3 na 1 rok																																																							
SLA4 na 1 rok																																																							
SLA5 na 1 rok																																																							
Výrobca a model + kód produktu:	Dell PowerStore 500T, 210AXXU																																																						

Príloha - Špecifikácia Serverov

Quantity	SKU (P/N)	Part Description
Server1		
1x PowerEdge R650xs (210-AZKL)		
Composants		
1	329-BGEZ	PowerEdge R650xs Motherboard
1	338-CBXJ	Intel Xeon Gold 6326 2.9G, 16C/32T, 11.2GT/s, 24M Cache, Turbo, HT (185W) DDR4-3200
1	379-BDSS	SAS/SATA Backplane
1	379-BDTE	No Rear Storage
1	379-BCSF	iDRAC, Factory Generated Password
1	379-BCQY	iDRAC Group Manager, Disabled
1	379-BEIC	8x2.5 Front Storage
1	321-BGQI	2.5 Chassis with up to 8 Hard Drives (SAS/SATA), 1 CPU
1	325-BCHH	Standard Bezel
1	330-BBTC	Riser Config 4, 1xOCP 3.0(x16)+ 1x16LP
1	343-BBRH	PowerEdge R650xs x8 Shipping Material
1	350-BCEN	Dell EMC Luggage Tag (x8 or x10 chassis)
1	350-BCEM	No Quick Sync
1	370-AAIP	Performance Optimized
1	370-AEVR	3200MT/s RDIMMs
8	370-AGDS	32GB RDIMM, 3200MT/s, Dual Rank 16Gb BASE
1	385-BBQV	iDRAC9, Enterprise 15G
3	400-AXTV	480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
1	403-BBMB	Emulex LPE 31002 Dual Port 16Gb Fibre Channel HBA, PCIe Low Profile
1	405-AAUZ	PERC H745 Controller, Front
1	412-AAVQ	MOD, THRM, CPU, HPR, 1U, R450/R650X
1	412-AAVV	MOD, FILLER, BLNK, CPU, R450/R650X
1	450-AIQX	Dual, Hot-plug, PSU (1+1), 800, Mixed Mode
2	450-AADY	C13 to C14, PDU Style, 10 AMP, 6.5 Feet (2m), Power Cord
1	461-AAIG	Trusted Platform Module 2.0 V3
1	293-10025	Asset Tag - ProSupport (Website, barcode, Onboard MacAddress)
1	293-10049	Order Configuration Shipbox Label (Ship Date, Model, Processor Speed, HDD Size, RAM)
1	540-BCNT	Broadcom 57412 Dual Port 10GbE SFP+, OCP NIC 3.0
1	750-ACFR	Front PERC Mechanical Parts, front load
1	770-BCJI	ReadyRails Sliding Rails Without Cable Management Arm
1	770-BDZL	Cable Management Arm
1	780-BCDS	Unconfigured RAID
Logiciel		
1	384-BBBH	Power Saving BIOS Settings
1	384-BCUB	High Performance Fan x5
1	631-AACK	No Systems Documentation, No OpenManage DVD Kit
Service		
1	647-10219	Partner Operations Support
1	709-BBIL	Next Business Day 36MONTHS
1	865-BBMY	ProSupport Next Business Day Onsite Service Initial, 36 Mesiac
Server2		
1x PowerEdge R650xs (210-AZKL)		
Composants		
1	329-BGEZ	PowerEdge R650xs Motherboard
1	338-CBXJ	Intel Xeon Gold 6326 2.9G, 16C/32T, 11.2GT/s, 24M Cache, Turbo, HT (185W) DDR4-3200
1	379-BDSS	SAS/SATA Backplane
1	379-BDTE	No Rear Storage
1	379-BCSF	iDRAC, Factory Generated Password
1	379-BCQY	iDRAC Group Manager, Disabled
1	379-BEIC	8x2.5 Front Storage
1	321-BGQI	2.5 Chassis with up to 8 Hard Drives (SAS/SATA), 1 CPU
1	325-BCHH	Standard Bezel
1	330-BBTC	Riser Config 4, 1xOCP 3.0(x16)+ 1x16LP
1	343-BBRH	PowerEdge R650xs x8 Shipping Material
1	350-BCEN	Dell EMC Luggage Tag (x8 or x10 chassis)
1	350-BCEM	No Quick Sync
1	370-AAIP	Performance Optimized
1	370-AEVR	3200MT/s RDIMMs
4	370-AGDS	32GB RDIMM, 3200MT/s, Dual Rank 16Gb BASE

1	385-BBQV	iDRAC9, Enterprise 15G
3	400-AXTV	480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
1	403-BBMB	Emulex LPE 31002 Dual Port 16Gb Fibre Channel HBA, PCIe Low Profile
1	405-AAUZ	PERC H745 Controller, Front
1	412-AAVQ	MOD,THRM,CPU,HPR,1U,R450/R650X
1	412-AAVV	MOD,FILLER,BLNK,CPU,R450/R650X
1	450-AIQX	Dual, Hot-plug, PSU (1+1), 800, Mixed Mode
2	450-AADY	C13 to C14, PDU Style, 10 AMP, 6.5 Feet (2m), Power Cord
1	461-AAIG	Trusted Platform Module 2.0 V3
1	293-10025	Asset Tag - ProSupport (Website, barcode, Onboard MacAddress)
1	293-10049	Order Configuration Shipbox Label (Ship Date, Model, Processor Speed, HDD Size, RAM)
1	540-BCOB	Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0
1	750-ACFR	Front PERC Mechanical Parts, front load
1	770-BCJI	ReadyRails Sliding Rails Without Cable Management Arm
1	770-BDZL	Cable Management Arm
1	780-BCDS	Unconfigured RAID
Logiciel		
1	384-BBBH	Power Saving BIOS Settings
1	384-BCUB	High Performance Fan x5
1	631-AACK	No Systems Documentation, No OpenManage DVD Kit
Service		
1	647-10219	Partner Operations Support
1	709-BBIL	Next Business Day 36MONTHS
1	865-BBMY	ProSupport Next Business Day Onsite Service Initial, 36 Mesiac
Server3		
1x PowerEdge R750 Server (210-AYCG)		
Composants		
1	329-BGJR	R750 Motherboard
1	329-BERC	Assembly BOSS Blank
1	338-CBWI	Intel Xeon Silver 4309Y 2.8G, 8C/16T, 10.4GT/s, 12M Cache, Turbo, HT (105W) DDR4-2666
1	379-BDTF	2.5 Chassis
1	379-BDSW	SAS/SATA/NVMe Capable Backplane
1	379-BDTE	No Rear Storage
1	379-BCSF	iDRAC,Factory Generated Password
1	379-BCQV	iDRAC Group Manager, Enabled
1	379-BDSR	No GPU Enablement
1	321-BGLQ	2.5 Chassis with up to 24 HDDS (SAS/SATA) including 4 Universal Slots for 1CPU
1	325-BCHU	Configuration
Large 2U Standard Bezel		
1	330-BBUY	Riser Config 8, 2x8, 2x16 slots
1	350-BCED	Dell EMC Luggage Tag
1	350-BBYX	No Quick Sync
1	370-AAIP	Performance Optimized
1	370-AEVR	3200MT/s RDIMMs
2	370-AGDS	32GB RDIMM, 3200MT/s, Dual Rank 16Gb BASE
1	385-BBQV	iDRAC9, Enterprise 15G
3	400-AXTV	480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
1	403-BBMB	Emulex LPE 31002 Dual Port 16Gb Fibre Channel HBA, PCIe Low Profile
1	405-AAUZ	PERC H745 Controller, Front
1	412-AAUY	Heatsink for 1 CPU configuration (CPU less than 165W)
2	450-AADY	C13 to C14, PDU Style, 10 AMP, 6.5 Feet (2m), Power Cord
1	450-AJEX	Dual, Hot-Plug, Power Supply 800W Redundant, D
1	461-AAIG	Trusted Platform Module 2.0 V3
1	293-10049	Order Configuration Shipbox Label (Ship Date, Model, Processor Speed, HDD Size, RAM)
1	293-10025	Asset Tag - ProSupport (Website, barcode, Onboard MacAddress)
1	481-BBFG	PowerEdge R750 Shipping Material
1	540-BCNT	Broadcom 57412 Dual Port 10GbE SFP+, OCP NIC 3.0
1	750-AABF	Power Saving Dell Active Power Controller
1	750-ADGK	Standard Fan x6
1	750-ADED	Front PERC Mechanical Parts, for 2.5 x24 SAS/SATA Chassis
1	770-BBBQ	ReadyRails Sliding Rails
1	770-BDRQ	Cable Management Arm, 2U
1	780-BCDS	Unconfigured RAID
Logiciel		
1	631-AACK	No Systems Documentation, No OpenManage DVD Kit
Service		

1	647-10219	Partner Operations Support
1	709-BBIM	Next Business Day 36MONTHS
1	865-BBMY	ProSupport Next Business Day Onsite Service Initial, 36 Mesiaace

Server4

1x PowerEdge R750 Server (210-AYCG)

Composants		
1	329-BGJR	R750 Motherboard
1	329-BERC	Assembly BOSS Blank
1	338-CBWI	Intel Xeon Silver 4309Y 2.8G, 8C/16T, 10.4GT/s, 12M Cache, Turbo, HT (105W) DDR4-2666
1	379-BDTF	2.5 Chassis
1	379-BDSW	SAS/SATA/NVMe Capable Backplane
1	379-BDTE	No Rear Storage
1	379-BCSF	iDRAC,Factory Generated Password
1	379-BCQV	iDRAC Group Manager, Enabled
1	379-BDSR	No GPU Enablement
1	321-BGLQ	2.5 Chassis with up to 24 HDDS (SAS/SATA) including 4 Universal Slots for 1CPU Config
1	325-BCHU	PowerEdge 2U Standard Bezel
1	330-BBUY	Riser Config 8, 2x8, 2x16 slots
1	350-BCED	Dell EMC Luggage Tag
1	350-BBYX	No Quick Sync
1	370-AAIP	Performance Optimized
1	370-AEVR	3200MT/s RDIMMs
2	370-AGDS	32GB RDIMM, 3200MT/s, Dual Rank 16Gb BASE
1	385-BBQV	iDRAC9, Enterprise 15G
3	400-AXTV	480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
1	403-BBMB	Emulex LPE 31002 Dual Port 16Gb Fibre Channel HBA, PCIe Low Profile
1	405-AAUZ	PERC H745 Controller, Front
1	412-AAUY	Heatsink for 1 CPU configuration (CPU less than 165W)
2	450-AADY	C13 to C14, PDU Style, 10 AMP, 6.5 Feet (2m), Power Cord
1	450-AJEX	Dual, Hot-Plug, Power Supply 800W Redundant, D
1	461-AAIG	Trusted Platform Module 2.0 V3
1	293-10049	Order Configuration Shipbox Label (Ship Date, Model, Processor Speed, HDD Size, RAM)
1	293-10025	Asset Tag - ProSupport (Website, barcode, Onboard MacAddress)
1	389-DYHB	PowerEdge Non BIS Marking
1	481-BBFG	PowerEdge R750 Shipping Material
1	540-BCOB	Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0
1	750-AABF	Power Saving Dell Active Power Controller
1	750-ADGK	Standard Fan x6
1	750-ADED	Front PERC Mechanical Parts, for 2.5 x24 SAS/SATA Chassis
1	770-BBBQ	ReadyRails Sliding Rails
1	770-BDRQ	Cable Management Arm, 2U
1	780-BCDS	Unconfigured RAID
Logiciel		
1	631-AACK	No Systems Documentation, No OpenManage DVD Kit
Service		
1	647-10219	Partner Operations Support
1	709-BBIM	Next Business Day 36MONTHS
1	865-BBMY	ProSupport Next Business Day Onsite Service Initial, 36 Mesiaace

Server5

1x PowerEdge R750 Server (210-AYCG)

Composants		
1	329-BGJR	R750 Motherboard
1	329-BERC	Assembly BOSS Blank
1	338-CBWI	Intel Xeon Silver 4309Y 2.8G, 8C/16T, 10.4GT/s, 12M Cache, Turbo, HT (105W) DDR4-2666
1	379-BDTF	2.5 Chassis
1	379-BDSW	SAS/SATA/NVMe Capable Backplane
1	379-BDTE	No Rear Storage
1	379-BCSF	iDRAC,Factory Generated Password
1	379-BCQV	iDRAC Group Manager, Enabled
1	379-BDSR	No GPU Enablement
1	321-BGLQ	2.5 Chassis with up to 24 HDDS (SAS/SATA) including 4 Universal Slots for 1CPU Config
1	325-BCHU	PowerEdge 2U Standard Bezel
1	330-BBUY	Riser Config 8, 2x8, 2x16 slots
1	350-BCED	Dell EMC Luggage Tag
1	350-BBYX	No Quick Sync
1	370-AAIP	Performance Optimized

1	370-AEVR	3200MT/s RDIMMs
2	370-AGDS	32GB RDIMM, 3200MT/s, Dual Rank 16Gb BASE
1	385-BBQV	iDRAC9, Enterprise 15G
3	400-AXTV	480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
1	403-BBMB	Emulex LPE 31002 Dual Port 16Gb Fibre Channel HBA, PCIe Low Profile
1	405-AAUZ	PERC H745 Controller, Front
1	412-AAUY	Heatsink for 1 CPU configuration (CPU less than 165W)
2	450-AADY	C13 to C14, PDU Style, 10 AMP, 6.5 Feet (2m), Power Cord
1	450-AJEX	Dual, Hot-Plug, Power Supply 800W Redundant, D
1	461-AAIG	Trusted Platform Module 2.0 V3
1	293-10049	Order Configuration Shipbox Label (Ship Date, Model, Processor Speed, HDD Size, RAM)
1	293-10025	Asset Tag - ProSupport (Website, barcode, Onboard MacAddress)
1	389-DYHB	PowerEdge Non BIS Marking
1	481-BBFG	PowerEdge R750 Shipping Material
1	540-BCOB	Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0
1	750-AABF	Power Saving Dell Active Power Controller
1	750-ADGK	Standard Fan x6
1	750-ADED	Front PERC Mechanical Parts, for 2.5 x24 SAS/SATA Chassis
1	770-BBBQ	ReadyRails Sliding Rails
1	770-BDRQ	Cable Management Arm, 2U
1	780-BCDS	Unconfigured RAID
Logiciel		
1	631-AACK	No Systems Documentation, No OpenManage DVD Kit
Service		
1	647-10219	Partner Operations Support
1	709-BBIM	Next Business Day 36MONTHS
1	865-BBMY	ProSupport Next Business Day Onsite Service Initial, 36 Mesiac
Server6		
1x PowerEdge T140 Server (210-AQSP)		
Composants		
1	329-BEQX	PowerEdge T140 MLK Motherboard
1	338-BUIY	Intel Xeon E-2224 3.4GHz, 8M cache, 4C/4T, turbo (71W)
1	379-BCRG	iDRAC, Factory Generated Password
1	379-BCQY	iDRAC Group Manager, Disabled
1	321-BDVW	MOD,CBL,SAS,PERC,HDD,T140
1	370-AAIP	Performance Optimized
1	370-AGNY	3200MT/s UDIMM
1	370-AGQW	8GB UDIMM, 3200MT/s, ECC
1	385-BBKT	iDRAC9, Enterprise
1	400-AVBD	1TB 7.2K RPM SATA 6Gbps 512n 3.5in Cabled Hard Drive
1	405-AANS	PERC H330+ RAID Controller, Adapter, Full Height
1	412-AAQD	Heatsink for 80W or less CPU
1	429-ABHR	No Internal Optical Drive
1	450-AADY	C13 to C14, PDU Style, 10 AMP, 6.5 Feet (2m), Power Cord
1	461-AAEM	Trusted Platform Module 2.0
1	293-10025	Asset Tag - ProSupport (Website, barcode, Onboard MacAddress)
1	293-10049	Order Configuration Shipbox Label (Ship Date, Model, Processor Speed, HDD Size, RAM)
1	542-BBBP	On-Board LOM
1	780-BCDI	No RAID
Logiciel		
1	384-BBBL	Performance BIOS Settings
1	631-AACK	No Systems Documentation, No OpenManage DVD Kit
Service		
1	647-10218	Partner Operations Support
1	709-BBHY	Next Business Day 12MONTHS
1	865-BBKQ	ProSupport Next Business Day Onsite Service Initial, 12 Mesiac
1	865-BBKR	ProSupport Next Business Day Onsite Service Extension, 24 Mesiac

Quantity	SKU (P/N)	Part Description
Storage1		
1x PowerStore 500T Customer Rack[Dell EMC PowerStore 500 T - EMEA]		
1	370-AFXQ	192GB Appliance DIMM 96GB Per Node
13	400-BGGM	P1 25X2.5 NVME SED SSD 3.84TB
1	450-AKHM	1450 WATT POWER SUPPLY PAIR
1	565-BBJP	16GB FC 4 PORT IO MODULE PAIR
Service		
1	647-10219	Partner Operations Support
1	683-25693	ProDeploy Plus for PowerStore 5XXT
1	528-BTZK	PowerStore Base SW
1	709-BCFM	Parts Only Warranty 12 Months, 12 Month(s)
1	865-BBYM	ProSupport and 4Hr Mission Critical Extension, 24 Month(s)
1	865-BBYN	ProSupport and 4Hr Mission Critical Initial, 12 Month(s)
2x Metro node Base[Metro node for PowerStore 500T PROMO EMEA]		
1	329-BDMR	OEM PowerEdge R640 XL Motherboard
2	338-BSWX	Intel Xeon Silver 4208 2.1G, 8C/16T, 9.6GT/s, 11M Cache, Turbo, HT (85W) DDR4-2400
1	379-BCQW	iDRAC Service Module (ISM), Pre-Installed in OS
1	379-BCQY	iDRAC Group Manager, Disabled
1	379-BDCO	Additional Processor Selected
1	321-BCYJ	2.5 Chassis with up to 8 Hard Drives and 3PCIe slots,SATA (No PERC)
1	325-BDZP	Bezel for metro node - PowerStore
1	330-BBGN	Riser Config 2, 3x16 LP
1	350-BBKB	No Quick Sync
1	350-BCCT	IDM/Personality Module for metro node
1	350-BCDY	Luggage Tag for metro node - PowerStore
1	370-AAIP	Performance Optimized
1	370-AEVR	3200MT/s RDIMMs
4	370-AEVQ	16GB RDIMM, 3200MT/s, Dual Rank
1	370-ABWE	DIMM Blanks for System with 2 Processors
1	385-BBKT	iDRAC9,Enterprise
1	400-AXTV	480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD
1	405-AACD	No Controller
2	406-BBMO	Emulex LPE 35002 Dual Port 32 Gb Fibre Channel HBA, PCIe Low Profile
2	407-BCBE	Dell EMC PowerEdge SFP+ SR Optic 10GbE 850nm
2	412-AAIQ	Standard 1U Heatsink
1	429-ABBF	No Internal Optical Drive for x4 and x8 HDD Chassis
1	450-AAGG	No Power Cord
1	450-AJSC	Dual, Hot-plug, Redundant Power Supply (1+1), 750W
1	461-AADZ	No Trusted Platform Module
1	470-AENQ	CMA KIT (PWR,LCOM,MGMT Cables Included)
1	540-BBVO	Intel X710 Quad Port 10GbE BASE-T Adapter, PCIe Low Profile
1	555-BCKP	Intel X710 Quad Port 10Gb DA/SFP+ Ethernet, Network Daughter Card
1	770-BCIO	1U Combo Drop-In/Stab-In Rails
1	780-BCDM	No RAID with Embedded SATA
1	528-BCBW	MAC Address Reporting Service
1	528-CNOH	Metro node Operating System=IA
1	528-CNPF	Local 10TB Capacity License=CA
Logiciel		
1	384-BBQJ	8 Standard Fans for R640
1	631-AACK	No Systems Documentation, No OpenManage DVD Kit
1	631-ACTH	Metro node Factory Installed Software
Service		
1	487-BGNS	ProSupport Mission Critical metro node Local Base Incl 10TB Software Support-Maint, 36 Month(s)
1	683-26309	ProDeploy for Metro Node Single Node Deployment
1	709-BCFC	Basic Next Business Day 12 Months, 12 Month(s)
1	199-BFID	ProSupport and 4HR Mission Critical Extension, 24 Month(s)
1	199-BFIE	ProSupport and 4HR Mission Critical Initial, 12 Month(s)
1x Metro node Software[Metro node Software for PowerStore EMEA]		
1	528-CR XR	Metro node PwrStr 500T METRO FB SW=IC
Service		
1	487-BGJX	ProSupport Mission Critical metro node Software Support-Maintenance, 36 Month(s)
Storage2		
1x PowerStore 500T Customer Rack[Dell EMC PowerStore 500 T - EMEA]		
1	370-AFXQ	192GB Appliance DIMM 96GB Per Node

7	400-BGGI	P1 25X2.5 NVME SED SSD 1.92TB
1	450-AKHM	1450 WATT POWER SUPPLY PAIR
1	565-BBJP	16GB FC 4 PORT IO MODULE PAIR
Service		
1	647-10219	Partner Operations Support
1	683-25693	ProDeploy Plus for PowerStore 5XXT
1	528-BTZK	PowerStore Base SW
1	709-BCFM	Parts Only Warranty 12 Months, 12 Month(s)
1	865-BBYM	ProSupport and 4Hr Mission Critical Extension, 24 Month(s)
1	865-BBYN	ProSupport and 4Hr Mission Critical Initial, 12 Month(s)
SAN1		
1x CTX MDS-9132T 8P/32P, 32Gb FC Switch with PSE airflow (1 PSU + 2 Fans, 8 x16Gb SFPs included)[Connectrix MDS-9132T - [EMEA_MDS9132T_38812_VP]]		
1	407-BCSJ	Connectrix MDS-9132T 32G FC 8 Port Upg Lic=MA
8	407-BCFX	Connectrix MDS 16Gb Fibre Channel Short Wave Switch Optic
1	450-AKRT	Connectrix MDS-9132T Power Supply (Port-Side Exhaust)
1	450-AKRL	Qty 2 9100 9200 Power Cord Europe
Logiciel		
2	384-BCVJ	Connectrix MDS-9132T Fan (Port-Side Exhaust)
Service		
1	647-10219	Partner Operations Support
1	683-23521	Certified Deployment Partner T2
1	709-BCLF	Parts Only Warranty 12 Months
1	865-BBWK	ProSupport and 4HR Mission Critical Extension, 24 Month(s)
1	865-BBWL	ProSupport and 4HR Mission Critical Initial, 12 Month(s)