

Vlastný návrh plnenia

Technická špecifikácia :

Popis tovaru	Počet	Merná jednotka	JC bez DPH	Spolu bez DPH	DPH 20 %	Spolu s DPH
Dell EMC Switch S4112F s 3 ročnou podporou ProSupport and Next Business Day Onsite Service alebo ekvivalent	2	ks	13 000,00	26 000,00	5 200,00	31 200,00
Dell Networking Dual Tray alebo ekvivalent	1	ks	175,00	175,00	35,00	210,00
Dell Networking N1548P s 2 ročnou podporou ProSupport and Next Business Day Onsite Service alebo ekvivalent	4	ks	4 500,00	18 000,00	3 600,00	21 600,00
Dell PE R650 s 3 ročnou podporou ProSupport and Next Business Day Onsite Service alebo ekvivalent	5	ks	44 500,00	222 500,00	44 500	267 000,00
Spolu za predmet zákazky				266 675,00	53 335,00	320 010,00

Podrobná technická špecifikácia :

	Konfigurácia 1ks prepínača S4112F
1	Dell EMC Switch S4112F, 12 x 10GbE SFP+, 3 x 100GbE QSFP28, IO to PSU, 2 x AC PSU
1	OS10 Enterprise, S4112F
2	Power Cord, PDU (Rack)
1	Dell Networking Cable, 100GbE, Q28 to Q28, Passive Copper Direct Attach, 1 Meter
2	Dell Networking, Transceiver, SFP+, 10GbE, SR, 850nm Wavelength, 300m Reach
6	Dell Networking, Cable, SFP+ to SFP+, 10GbE, Copper Twinax Direct Attach Cable, 3 Meter
1	3Yr ProSupport and Next Business Day On-Site Service

	1x Tray na 2 prepínače S4112F
1	Dell Networking Dual Tray, one Rack Unit, 4-post rack only, S4112

	Konfigurácia 1ks prepínača N1548P
1	Dell Networking N1548P, PoE+, 48x 1GbE + 4x 10GbE SFP+ fixed ports, Stacking, IO to PSU airflow, AC
1	European 250V C15 Power Cord
1	2Yr ProSupport and Next Business Day Onsite Service

	Konfigurácia 1ks servera PE R650
1	PowerEdge R650 Server
1	2.5" Chassis with up to 10 Hard Drives (SAS/SATA), 1 PCIe Slot, 1 CPU
1	No Rear Storage
1	SAS/SATA Backplane
1	Trusted Platform Module 2.0 V3
1	Intel® Xeon® Gold 6326 2.9G, 16C/32T, 11.2GT/s, 24M Cache, Turbo, HT (185W) DDR4-3200

1	Heatsink for 1 CPU configuration (CPU more than 165W)
16	32GB RDIMM, 3200MT/s, Dual Rank, 16Gb BASE x8
1	C7, Unconfigured RAID for HDDs or SSDs (Mixed Drive Types Allowed)
1	Front PERC H755 Rear Load
6	1.92TB SSD SAS 12Gbps MU FIPS-140 PM6 512e 2.5in Hot-Plug 3 DWPD
1	3 High Performance Fans for 1 CPU
1	Dual, Hot-plug, Power Supply Fault Tolerant Redundant (1+1), 1400W, Mixed Mode
2	Rack Power Cord 2M (C13/C14 10A)
1	Riser Config 0, 1CPU, Half Length, Low Profile, 1 x16 Slot
1	PowerEdge R650 Motherboard with Broadcom 5720 Dual Port 1Gb On-Board LOM
1	iDRAC9, Enterprise 15G
1	Broadcom 57412 Dual Port 10GbE SFP+, OCP NIC 3.0
1	LCD Bezel for x8 and x10 Chassis
1	BOSS-S2 controller card + with 2 M.2 240GB (RAID 1)
1	No Quick Sync
1	iDRAC, Factory Generated Password
1	iDRAC Group Manager, Enabled
1	ReadyRails Sliding Rails With Cable Management Arm
1	PowerEdge R650 Shipping EMEA2 (English/Slovenian/Slovakian/Polish/Czech/Hungar/Greek/Arab)
1	Order Configuration Shipbox Label (Ship Date, Model, Processor Speed, HDD Size, RAM)
1	ProSupport and Next Business Day Onsite Service, 36 Month(s)
1	Keep Your Hard Drive For Enterprise, 36 Month(s)
1	Asset Tag - ProSupport (Website, barcode, Onboard MacAddress)

V Bratislave, dňa 20.06.2022

Mgr. Alžbeta Bieliková
osoba oprávnená konať za uchádzača